

Status:	Ok
Approval:	10.11.2023

Classification	Public series
Product type:	Foam abrasives
Main industries:	Building Interior
Further industries:	Kitchens Windows and Doors Marine


Product profile	
Grit type:	Aluminium oxide
Grit range (total):	180; 240; 320
Backing:	Mesh
Coating:	Mechanical
Bonding:	Elastic binder
Special coating:	
Equipment:	




Properties		Technology
Removal rate:	8 - high	
Lifetime:	9 - very long	
Finishing:	8 - good	
Flexibility:	10 - highly flexible	
Contact pressure:	7 - strong	

Advantages	
Building Interior:	<ul style="list-style-type: none"> - Maximum useful life - Highly adaptable to contours, curves and profiles - Low clogging - Can be used many times - Consistent performance throughout the life of the product - Can be used wet or dry

Applications	
Building Interior:	<ul style="list-style-type: none"> - Sanding off old varnish, paints and stains - Sanding off raised wooden fibres - Keying surfaces for better paint adhesion

Material		
Building Interior:	<ul style="list-style-type: none"> Bodyfiller Lacquers Lacquers Lacquers Lacquers Lacquers Metals Mineral materials Old lacquer Old paint Paints Plaster Primer filler Wood Wood 	<ul style="list-style-type: none"> <input type="radio"/> Acrylic glass <input type="radio"/> Plastics <input type="radio"/> Melamine sheet <input type="radio"/> Bodyfiller <input checked="" type="radio"/> Water-based lacquer <input checked="" type="radio"/> UV lacquer <input checked="" type="radio"/> Polyester lacquer <input type="radio"/> NC lacquer <input checked="" type="radio"/> PU lacquer <input checked="" type="radio"/> Stainless steel (inox) <input type="radio"/> Solid surface material <input checked="" type="radio"/> Old lacquer <input checked="" type="radio"/> Old paint <input checked="" type="radio"/> Colour <input type="radio"/> Plaster <input checked="" type="radio"/> Primer filler <input checked="" type="radio"/> Hard wood <input checked="" type="radio"/> Soft wood

Conversion forms	Upper conversion	Lower conversion
	Sheet	- Half sheets

Application	Superordinate group	Subgroup
	Manual sanding	Manual sanding
	Manual sanding	Hand sanding for profiles
	Manual sanding	Hand sanding for edges
Cut:	Dry application, Wet sanding	

Details	
No suitability for:	
Sanding recommendation:	
Safety recommendation:	Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety



Communication	
Claim:	Robust and highly versatile
Copy:	The double-sided 7988 siastrong can be used in a wide variety of applications. Its perforation ensures sharp contours and makes precise sanding easy, even in hard-to-reach places. The robust abrasive is washable, hard-wearing and durable.
Image material:	Product Top View (PTV) Front side: ID Rear side: ID
	Application image Building Interior: ID 115582
	Product show:
	Macro shot:
	Packaging image:
	Product group image: ID 115654

- Main application
- Secondary application