

According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

Page 1 of 11

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

siachrome CUT

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture

Automotive care products

1.3. Details of the supplier of the safety data sheet

Company name:	Sia Abrasives Industries AG	
Street:	Mühlwiesenstrasse 20	
Place:	CH-8501 Frauenfeld/Schweiz	
Telephone: e-mail: Internet:	+41 (0)52 724 41 11 msds.ch@sia-abrasives.com www.sia-abrasives.com	Telefax:+41 (0)52 724 45 45
<u>1.4. Emergency telephone</u> number:	Toxzentrum Zürich 0041 44 251 51 51	

number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EG) Nr. 1272/2008

This mixture is not classified as hazardous in accordance with GB CLP Regulation.

2.2. Label elements

Regulation (EG) Nr. 1272/2008

Hazard components for labelling

This product has been treated with biocides for preservation.

Precautionary statements

Keep out of reach of children.

Special labelling of certain mixtures

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2 -methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction. Safety data sheet available on request.

EUH210

EUH208

2.3. Other hazards

P102

No information available.

SECTION 3: Composition/information on ingredients

3.2. Mixtures



According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

Page 2 of 11

Hazardous components

CAS No	Chemical name		Chemical name			
	EC No	Index No	REACH No			
	Classification (Regulation (EG) Nr.					
	Hydrocarbons, C10-C13, n-alkanes	s, isoalkanes, cyclics, < 0,1% Benzer	ne	15 - < 20 %		
	918-481-9		01-2119457273-39			
	Asp. Tox. 1; H304 EUH066					
8042-47-5	white mineral oil (petroleum)		1 - < 5 %			
	232-455-8		01-2119487078-27			
	Asp. Tox. 1; H304					
55965-84-9	mixture of 5-chloro-2-methyl-2H-iso 2-methyl-2H-isothiazol-3-one (EG	nd	< 0.1 %			
	611-341-5	613-167-00-5				
	Acute Tox. 2, Acute Tox. 2, Acute Tox. 3, Skin Corr. 1C, Eye Dam. 1, Skin Sens. 1A, Aquatic Acute 1, Aquatic Chronic 1; H330 H310 H301 H314 H318 H317 H400 H410 EUH071					

Full text of H and EUH statements: see section 16.

Specific Conc. Limits, M-factors and ATE

CAS No	EC No	Chemical name	Quantity
	Specific Cond	c. Limits, M-factors and ATE	
	918-481-9	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclics, < 0,1% Benzene	15 - < 20 %
	dermal: LD5	0 = >5000 mg/kg; oral: LD50 = >5000 mg/kg	
8042-47-5	232-455-8	white mineral oil (petroleum)	1 - < 5 %
	dermal: LD5) = >2000 mg/kg; oral: LD50 = >5000 mg/kg	
55965-84-9	611-341-5	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)	< 0.1 %
	= >141 mg/kg 0,06 - < 0,6 1A; H317: >= Aquatic Acute	TE = 0,5 mg/l (vapours); inhalation: ATE = 0,05 mg/l (dusts or mists); dermal: LD50 g; oral: LD50 = 66 mg/kg Skin Corr. 1C; H314: >= 0,6 - 100 Skin Irrit. 2; H315: >= Eye Dam. 1; H318: >= 0,6 - 100 Eye Irrit. 2; H319: >= 0,06 - < 0,6 Skin Sens. 0,0015 - 100 e 1; H400: M=100 nic 1; H410: M=100	

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

No special measures are necessary. When in doubt or if symptoms are observed, get medical advice.

After inhalation

Provide fresh air. In case of respiratory tract irritation, consult a physician.

After contact with skin

After contact with skin, wash immediately with plenty of water and soap. Take off contaminated clothing and wash it before reuse.

After contact with eyes

Rinse immediately carefully and thoroughly with eye-bath or water.

After ingestion

Rinse mouth immediately and drink plenty of water. Do NOT induce vomiting. Call a doctor.

4.2. Most important symptoms and effects, both acute and delayed

No information available.

4.3. Indication of any immediate medical attention and special treatment needed

Treat symptomatically.



According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

Page 3 of 11

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media

Foam. Dry extinguishing powder. Carbon dioxide (CO2). Water spray jet. Co-ordinate fire-fighting measures to the fire surroundings.

Unsuitable extinguishing media

Full water jet

5.2. Special hazards arising from the substance or mixture

No special measures are necessary.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Collect contaminated fire extinguishing water separately. Do not allow entering drains or surface water.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General advice

Provide adequate ventilation. Do not breathe gas/fumes/vapour/spray. Avoid contact with skin, eyes and clothes. Use personal protection equipment.

For non-emergency personnel

Remove all sources of ignition. Ventilate affected area. Wear personal protection equipment (refer to section 8).

For emergency responders

Wear breathing apparatus if exposed to vapours/dusts/aerosols. Use personal protection equipment. Tested protective gloves must be worn: Recommended material: NBR (Nitrile rubber). Unsuitable material: PVC (polyvinyl chloride)

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

6.3. Methods and material for containment and cleaning up

For containment

Collect spillage. Stop leak if safe to do so. Cover drains.

For cleaning up

Absorb with liquid-binding material (sand, diatomaceous earth, acid- or universal binding agents). Treat the recovered material as prescribed in the section on waste disposal.

Other information

Use non-sparking tools. Clean contaminated articles and floor according to the environmental legislation.

6.4. Reference to other sections

Safe handling: see section 7 Personal protection equipment: see section 8 Disposal: see section 13

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Advice on safe handling

No special measures are necessary. Minimum standard for preventive measures while handling with working materials are specified in the TRGS 500.

ABRASIVES

Safety Data Sheet

According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

Page 4 of 11

Advice on protection against fire and explosion

No special fire protection measures are necessary. Only use the material in places where open light, fire and other flammable sources can be kept away.

Advice on general occupational hygiene

Take off contaminated clothing. Wash hands before breaks and after work. When using do not smoke. When using do not eat or drink. Avoid contact with skin, eyes and clothes. Avoid breathing dust/fume/gas/mist/vapours/spray.

7.2. Conditions for safe storage, including any incompatibilities

Requirements for storage rooms and vessels

Keep only in the original container in a cool, well-ventilated place. Keep container tightly closed.

Hints on joint storage

Do not store together with: Oxidising agent. Strong acid. Strong alkali.

Further information on storage conditions

Recommended storage temperature: 15-25°C

7.3. Specific end use(s)

Automotive care products

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Exposure limits (EH40)

CAS No	Substance	ppm	mg/m³	fibres/ml	Category	Origin
1344-28-1	Aluminium oxides, respirable dust	-	4		TWA (8 h)	WEL
56-81-5	Glycerol, mist	-	10		TWA (8 h)	WEL

DNEL/DMEL values

CAS No	Substance			
DNEL type		Exposure route	Effect	Value
1344-28-1	aluminium oxide			
Worker DNEL	long-term	inhalation	local	15,6 mg/m ³
Consumer DN	EL, long-term	oral	systemic	6,2 mg/kg bw/day
8042-47-5	white mineral oil (petroleum)			
Consumer DN	EL, long-term	inhalation	systemic	35 mg/m³
Consumer DN	EL, long-term	dermal	systemic	93 mg/kg bw/day
Worker DNEL	long-term	inhalation	systemic	160 mg/m ³
Worker DNEL	long-term	dermal	systemic	220 mg/kg bw/day
Consumer DN	EL, long-term	oral	systemic	40 mg/kg bw/day
1344-28-1	aluminium oxide			
Consumer DN	EL, long-term	oral	systemic	3,29 mg/kg bw/day
Worker DNEL, long-term		inhalation	local	15,63 mg/m³
56-81-5	glycerol			
Worker DNEL	long-term	inhalation	local	220 mg/m ³



According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

Page 5 of 11

PNEC values

CAS No	Substance	
Environmenta	al compartment	Value
1344-28-1	aluminium oxide	
Freshwater		0,0749 mg/l
Micro-organis	sms in sewage treatment plants (STP)	20 mg/l
1344-28-1	aluminium oxide	
Freshwater		0,0749 mg/l
Micro-organis	sms in sewage treatment plants (STP)	20 mg/l
56-81-5	glycerol	
Micro-organis	sms in sewage treatment plants (STP)	1000 mg/l

8.2. Exposure controls



Appropriate engineering controls

Use only in well-ventilated areas.

Individual protection measures, such as personal protective equipment

Eye/face protection

Wear eye/face protection.

Hand protection

When handling with chemical substances, protective gloves must be worn with the CE-label including the four control digits. The quality of the protective gloves resistant to chemicals must be chosen as a function of the specific working place concentration and quantity of hazardous substances. For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. Tested protective gloves must be worn.

Recommended glove articles: HyFlex® Foam (EN 420, EN 388 (3131)).

Skin protection

Wear suitable protective clothing.

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

Environmental exposure controls

No special environmental measures are necessary. Do not allow uncontrolled discharge of product into the environment.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state: Colour: Odour:	Liquid light yellow characteristic	
Melting point/freezing point:		not determined
Boiling point or initial boiling point and		100 °C
boiling range:		
Flammability		
Solid/liquid:		not applicable
Gas:		not applicable
Lower explosion limits:		0,5 vol. %



According to Regulation (EG) Nr. 1907/2006

siachrome CUT Revision date: 30.11.2022 Page 6 of 11 Upper explosion limits: 7 vol. % Flash point: >61 °C Auto-ignition temperature: >200 °C Decomposition temperature: not determined pH-Value (at 20 °C): 7,8 Viscosity / kinematic: >20,5 mm²/s (at 40 °C) Water solubility: completely miscible Solubility in other solvents not determined Partition coefficient n-octanol/water: not determined Vapour pressure: 0.6 hPa (at 20 °C) Vapour pressure: not determined Density (at 20 °C): 1,01 g/cm³ Relative density: not determined Bulk density: not determined 9.2. Other information Information with regard to physical hazard classes Oxidizing properties Not oxidising. Other safety characteristics Solvent content: 25.49 % 25000-30000 mPa·s Viscosity / dynamic: (at 20 °C)

SECTION 10: Stability and reactivity

10.1. Reactivity

No hazardous reaction when handled and stored according to provisions.

10.2. Chemical stability

The product is stable under storage at normal ambient temperatures.

10.3. Possibility of hazardous reactions

No known hazardous reactions.

10.4. Conditions to avoid

Only use the material in places where open light, fire and other flammable sources can be kept away.

10.5. Incompatible materials

Oxidising agent. Strong acid. Strong alkali.

10.6. Hazardous decomposition products

No known hazardous decomposition products.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in CLP Regulation

Toxicocinetics, metabolism and distribution

No information available.

Acute toxicity

Based on available data, the classification criteria are not met.



According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

Page 7 of 11

CAS No	Chemical name					
	Exposure route	Dose		Species	Source	Method
	Hydrocarbons, C10-C1	3, n-alkanes	, isoalkanes, c	cyclics, < 0,1% Benze	ene	
	oral	LD50 mg/kg	>5000	Rat	ECHA	OECD TG 401
	dermal	LD50 mg/kg	>5000	Rabbit	ECHA	OECD TG 402
8042-47-5	white mineral oil (petroleum)					
	oral	LD50 mg/kg	>5000	Rat	ECHA	OECD 401
	dermal	LD50 mg/kg	>2000	Rabbit	ECHA	OECD 402
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)					iazol-3-one (EG No.
	oral	LD50	66 mg/kg	Rat	Thor	
	dermal	LD50 mg/kg	>141		Thor	
	inhalation vapour	ATE	0,5 mg/l			
	inhalation dust/mist	ATE	0,05 mg/l			

Irritation and corrosivity

Based on available data, the classification criteria are not met.

Sensitising effects

Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.

Carcinogenic/mutagenic/toxic effects for reproduction

Based on available data, the classification criteria are not met.

STOT-single exposure

Based on available data, the classification criteria are not met.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Based on available data, the classification criteria are not met.

Specific effects in experiment on an animal

No information available.

Additional information on tests

The mixture is classified as not hazardous according to regulation (EC) No 1272/2008 [CLP].

SECTION 12: Ecological information

12.1. Toxicity

Based on available data, the classification criteria are not met.



Page 8 of 11

According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

CAS No	Chemical name						
	Aquatic toxicity	Dose		[h] [d]	Species	Source	Method
	Hydrocarbons, C10-C13,	n-alkanes, i	soalkanes, c	yclics, <	0,1% Benzene		
	Acute fish toxicity	LC50 mg/l	>1000	96 h	Oncorhynchus mykiss (Rainbow trout)	ECHA	OECD 203
	Acute algae toxicity	ErC50 mg/l	>1000	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EC50 mg/l	>1000	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
8042-47-5	white mineral oil (petrole	um)					
	Acute fish toxicity	LL50 mg/l	>1000	96 h	Leuciscus idus (golden orfe)	ECHA	OECD 203
	Acute algae toxicity	ErC50 mg/l	>100	72 h	Pseudokirchneriella subcapitata	ECHA	OECD 201
	Acute crustacea toxicity	EL50 mg/l	>100	48 h	Daphnia magna (Big water flea)	ECHA	OECD 202
	Algae toxicity	NOEC mg/l	>=100	72 d	Pseudokirchneriella subcapitata	ECHA	OECD 201
55965-84-9	mixture of 5-chloro-2-meth 220-239-6) (3:1)	nyl-2H-isoth	iazol-3-one (EG No. 2	247-500-7) and 2-methyl-	2H-isothiazol-3-one	e (EG No.
	Acute fish toxicity	LC50 mg/l	0,22	96 h	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 203
	Acute algae toxicity	ErC50 mg/l	0,048	72 h	Pseudokirchneriella subcapitata	Thor	OECD 201
	Acute crustacea toxicity	EC50	0,1 mg/l	48 h	Daphnia magna (Big water flea)	Thor	OECD 202
	Fish toxicity	NOEC mg/l	0,098	28 d	Oncorhynchus mykiss (Rainbow trout)	Thor	OECD 210
	Algae toxicity	NOEC mg/l	0,0012	3 d	Pseudokirchneriella subcapitata	Thor	OECD 201
	Crustacea toxicity	NOEC mg/l	0,004	21 d	Daphnia magna (Big water flea)	Thor	OECD 211
	Acute bacteria toxicity	(EC50 mg/l)	7,92	3 h	Activated sludge		OECD 209

12.2. Persistence and degradability

The substances in the mixture do not meet the PBT/vPvB criteria according to REACH, annex XIII.

CAS No	Chemical name						
	Method	Value	d	Source			
	Evaluation						
	Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cyclic	s, < 0,1% Benzene					
	OECD 301 F	80%	28	ECHA			
	Readily biodegradable (according to OECD criteria)).		-			
8042-47-5	white mineral oil (petroleum)						
	OECD 301F	31 %	28	ECHA			
	Not readily biodegradable (according to OECD crite	eria)					
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)						
	OECD 301 A	>70 %	28	Thor			
	Readily biodegradable (according to OECD criteria)).					
	OECD 301 D	>60%		Thor			
	Readily biodegradable (according to OECD criteria)).					



According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

Page 9 of 11

12.3. Bioaccumulative potential

The product has not been tested.

Partition coefficient n-octanol/water

CAS No	Chemical name	Log Pow
8042-47-5	white mineral oil (petroleum)	>4

BCF

CAS No	Chemical name	BCF	Species	Source
55965-84-9	mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1)	3,16		EPIWIN, S 1177

12.4. Mobility in soil

The product has not been tested.

12.5. Results of PBT and vPvB assessment

The substances in the mixture do not meet the PBT/vPvB criteria according to UK REACH.

The product has not been tested.

12.6. Endocrine disrupting properties

This product does not contain a substance that has endocrine disrupting properties with respect to non-target organisms as no components meets the criteria.

12.7. Other adverse effects

No information available.

Further information

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Disposal recommendations

Do not allow to enter into surface water or drains. Do not allow to enter into soil/subsoil. Dispose of waste according to applicable legislation.

Contaminated packaging

Non-contaminated packages may be recycled.

SECTION 14: Transport information

Land transport (ADR/RID)

 14.1. UN number or ID number:

 14.2. UN proper shipping name:

 14.3. Transport hazard class(es):

 14.4. Packing group:

 Inland waterways transport (ADN)

 14.1. UN number or ID number:

 14.2. UN proper shipping name:

 14.3. Transport hazard class(es):

 14.4. Packing group:

Marine transport (IMDG) 14.1. UN number or ID number:

14.2. UN proper shipping name: 14.3. Transport hazard class(es): No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.

No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation. No dangerous good in sense of this transport regulation.



According to Regulation (EG) Nr. 1907/2006

siachrome CUT						
Page 10 of 11						

Restrictions on use (REACH, annex XVII):	
Entry 75	
2010/75/EU (VOC):	15,001 % (151,508 g/l)
2004/42/EC (VOC):	15,001 % (151,508 g/l)
Information according to 2012/18/EU (SEVESO III):	Not subject to 2012/18/EU (SEVESO III)
Additional information	

Additional information

To follow: 850/2004/EC, 79/117/EEC, 689/2008/EC

National regulatory information

Water hazard class (D):	1 - slightly hazardous to water
(EU) EINECS/ELINCS/NLP:	yes

15.2. Chemical safety assessment

Chemical safety assessments for substances in this mixture were not carried out.

SECTION 16: Other information

Changes

This data sheet contains changes from the previous version in section(s): 1,6,7,9,15.

Abbreviations and acronyms

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road) IMDG: International Maritime Code for Dangerous Goods IATA: International Air Transport Association GHS: Globally Harmonized System of Classification and Labelling of Chemicals EINECS: European Inventory of Existing Commercial Chemical Substances ELINCS: European List of Notified Chemical Substances CAS: Chemical Abstracts Service LC50: Lethal concentration, 50%

Relevant H and EUH statements (number and full text)

H301 Toxic if swallowed.

H304 May be fatal if swallowed and enters airways.



According to Regulation (EG) Nr. 1907/2006

siachrome CUT

Revision date: 30.11.2022

Page 11 of 11

H310	Fatal in contact with skin.
H314	Causes severe skin burns and eye damage.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H330	Fatal if inhaled.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.
EUH066	Repeated exposure may cause skin dryness or cracking.
EUH071	Corrosive to the respiratory tract.
EUH208	Contains mixture of 5-chloro-2-methyl-2H-isothiazol-3-one (EG No. 247-500-7) and 2
	-methyl-2H-isothiazol-3-one (EG No. 220-239-6) (3:1). May produce an allergic reaction.
EUH210	Safety data sheet available on request.

Further Information

The above information describes exclusively the safety requirements of the product and is based on our present-day knowledge. The information is intended to give you advice about the safe handling of the product named in this safety data sheet, for storage, processing, transport and disposal. The information cannot be transferred to other products. In the case of mixing the product with other products or in the case of processing, the information on this safety data sheet is not necessarily valid for the new made-up material.

Identified uses

No	Short title	LCS	SU	PC	PROC	ERC	AC	TF	Specification
1	Formulation or re-packing	F	-	-	8a, 9	2	-	-	
2	Automotive care products, Industrial uses	IS	-	-	7, 10, 17	4	-	-	
3	Automotive care products, Professional uses	PW	-	-	10, 11, 17	8a	-	-	
4	Automotive care products, Consumer use	С	-	31	-	8a	-	-	
LCS: L	ife cycle stages	-	-	5	SU: Sectors of u	ise		-	-
PC: Pr	PC: Product categories PROC: Process categories								
ERC: Environmental release categories AC: A				AC: Article cate	gories				
TF: Technical functions									

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)