Technical data sheet
1950 siaspeed

Status:	Ok
Approval:	01.07.2026

Classification	Public series
Product type:	Coated abrasives
Main industries:	Automotive Aerospace Building Interior Furniture Production
Further industries:	Trucks Rail Marine Bus Wind Power Kitchens

Product profile		
Grit type:	Mixed grit with ceramic content Aluminium oxide White aluminium oxide	40 – 80 P100 – P400 P500 – 1500
Grit range (total):	40; 60-1500	P100 – P600 FEPA P / ISO 6344
Backing:	Paper (FSC™-certified) Film	40 – 600 800 – 1500
Coating:	Electrostatic Electrostatic open Special process	40 – 180 220 – 600 800 – 1500
Bonding:	Resin over resin	
Special coating:	Stearate	from 80
Equipment:		

Properties		**Technology**
Removal rate:	8 - high	- Open coating - Plain - S Performance - siafast - siasoft
Lifetime:	8 - long	
Finishing:	8 - good	
Flexibility:	7 - flexible	
Contact pressure:		

Advantages	
Building Interior:	- A versatile all-round product - High performance for stock removal - Longest lifetime - Minimal clogging thanks to open coating in 220 - 600 grit range
Furniture Production:	- Homogeneous sanding finish - Uniform abrasive structure on film - Excellent surface quality - Ideal for highly polishable surfaces

Advantages	
Automotive:	- Very high stock removal rates and excellent finish - Performance-enhancing grit mix with ceramic aluminium oxide in 40 - 80 grit range - Minimal clogging thanks to open coating in 220 - 600 grit range - Long lifetime - Lower abrasive consumption - Versatile all-round product with an attractive range of options
Aerospace:	- High-performance abrasives - High performance for stock removal - Long lifetime - A versatile all-round product - Lower abrasive consumption - Homogeneous sanding finish

Applications	
Building Interior:	- Keying or sanding surfaces - Sanding off old paint and varnish - Keying smoothed surfaces - Fine sanding of surfaces - Flatting uneven areas
Furniture Production:	- Preparation for polishing with long/cross belt (stationary)
Automotive:	- Sanding of coatings and impurities - Sanding out unevenness at the edges of repaired surfaces - Flatting of bodyfiller and composite materials - Fine sanding of primer filler - Keying of old and new lacquers - Producing a matt finish on old and new lacquers for blending - Removal of orange peel effect and dust inclusions - Preparation for polishing on high-gloss surfaces
Aerospace:	- Keying of polyesters and composites - Sanding out feather edges, flash rust and stone chips - Shaping of bodyfillers and primer fillers - Keying of new components and factory primers - Sanding of old lacquer - Producing a matt finish on old and new lacquers for blending - Flatting of bodyfiller and primer filler - Removal of orange peel effect and dust inclusions - Preparation for polishing on high-gloss surfaces

Material		
Building Interior:		○ Plastics
	Bodyfiller	● Bodyfiller
	Dry wall lining boards	○ Dry wall lining boards
	Lacquers	● Lacquer
	Mineral materials	● Solid surface material
	Plaster	○ Plaster
	Primer filler	● Primer filler
	Wood	● Hard wood
	Wood	● Soft wood
	Wood	○ Resinous wood
Furniture Production:	Coatings	● Lacquer
	Plastics	● Solid surface material
Automotive:	Bodyfiller	● Bodyfiller
	Composites	● Glass-fibre reinforced plastic (GRP)
	Gelcoats	● Gelcoat polyester
	Lacquers	● Lacquer
	Lacquers	● Old lacquer
	Paints	● Colour
	Plastics	● Plastics
	Plastics	● Acrylic glass
	Primer filler	● Primer filler
	Primers	● Primer coat
	Primers	● Epoxy primer coat
	Primers	● Cathodic dip primer coat
Aerospace:		● Colour
		● Primer filler
		● Old lacquer
	Acrylic glass (Plexiglass)	● Acrylic glass
	Bodyfiller	● Bodyfiller
	Composites	● Glass-fibre reinforced plastic (GRP)
	Gelcoats	● Gelcoat polyester
	Lacquers	● Lacquer
	Plastics	● Plastics
	Primers	● Primer coat
	Primers	● Epoxy primer coat
	Primers	● Cathodic dip primer coat

Conversion forms	Upper conversion	Lower conversion
	Rolls	- Jumbolino - Paper rolls - siafast rolls - siasoft rolls
	Strips	- siafast strips - siasoft Pads

Technical data sheet
1950 siaspeed

Conversion forms	Upper conversion	Lower conversion
	Delta and polygons	- Delta and polygons
	Discs	- siafast discs - siasoft discs - Daisy discs - Self-adhesive discs - Various discs
	Belts	- Hand sanding belts and sleeves (width: 30–390 mm/length: up to 950 mm) - Narrow, edge and long belts (width: 25–399 mm/length: up to 10,700 mm) - Power file belts (width: 6-30 mm/length: up to 950 mm)

Application	Superordinate group	Subgroup
	Portable machine sanding	random orbital sander
	Portable machine sanding	Orbital sanders
	Portable machine sanding	Delta sander
	Manual sanding	Manual sanding
	Manual sanding	Hand sanding with sanding block
	Stationary machine sanding	Rolls
Cut:	Dry application	

Details	
No suitability for:	- glass sanding - Wet sanding - Stone grinding
Sanding recommendation:	
Safety recommendation:	Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety - Pay attention to the abrasives safety data sheet (available from sia Abrasives) - Follow the general FEPA safety recommendations - Use eye and face protection - Use an effective dust extraction unit or wear a fine dust mask

Communication			
Claim:	For a perfect finish at full speed		
Copy:	The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.		
Image material:	Product Top View (PTV)	Front side: Rear side:	ID 1898 ID 1841
	Application image	Building Interior: Furniture Production: Automotive: Aerospace:	ID 342 ID 341 ID 8855 ID 9271
	Product show:		
	Macro shot:		
	Packaging image:		
	Product group image:		ID 1656

● Main application
○ Secondary application