

Status:	Ok
Approval:	15.04.2024

Classification	Public series
Product type:	Coated abrasives
Main industries:	Automotive Aerospace Building Interior Furniture Production
Further industries:	Trucks Rail Marine Bus Wind Power Kitchens

Product profile		
Grit type:	Mixed grit with ceramic content Semi-friable aluminium oxide / blue-fired White aluminium oxide	40 – 80 P100 – P400 P500 – P1500
Grit range (total):	40; 60-1500	P100 – P1500 FEPA P / ISO 6344
Backing:	Paper (FSC-certified) Film	40 – P600 P800 – P1500
Coating:	Electrostatic	40 - P180
	Electrostatic open	P220 – P600
	Special process	P800 – P1500
Bonding:	Resin over resin	
Special coating:	Stearate	from 80
Equipment:		

Properties		Technology
Removal rate:	8 - high	- Open coating
Lifetime:	8 - long	- Plain
Finishing:	7 - good	- S Performance
Flexibility:	7 - flexible	- siafast
Contact pressure:		- siasoft

Advantages	
Building Interior:	 A versatile all-round product High performance for stock removal Longest lifetime Minimal clogging thanks to open coating in 220 - 600 grit range
Furniture Production:	 Homogeneous sanding finish Uniform abrasive structure on film Excellent surface quality Ideal for highly polishable surfaces



Advantages	
Automotive:	 Very high stock removal rates and excellent finish Performance-enhancing grit mix with ceramic aluminium oxide in 40 - 80 grit range Minimal clogging thanks to open coating in 220 - 600 grit range Extremely long lifetime Lower abrasive consumption Versatile all-round product with an attractive range of options
Aerospace:	 High-performance abrasives High performance for stock removal Longest lifetime A versatile all-round product Lower abrasive consumption Homogeneous sanding finish

Applications		
Building Interior:	 Keying or sanding surfaces Sanding off old paint and varnish Keying smoothed surfaces Fine sanding of surfaces Flatting uneven areas 	
Furniture Production:	- Preparation for polishing with long/cross belt (stationary)	
Automotive:	 Sanding of coatings and impurities Sanding out unevenness at the edges of repaired surfaces Flatting of bodyfiller and composite materials Fine sanding of primer filler Keying of old and new lacquers Producing a matt finish on old and new lacquers for blending Removal of orange peel effect and dust inclusions Preparation for polishing on high-gloss surfaces 	
Aerospace:	 Keying of polyesters and composites Sanding out feather edges, flash rust and stone chips Shaping of bodyfillers and primer fillers Keying of new components and factory primers Sanding of old lacquer Producing a matt finish on old and new lacquers for blending Flatting of bodyfiller and primer filler Removal of orange peel effect and dust inclusions Preparation for polishing on high-gloss surfaces 	



Material		
Building Interior:		 Plastics
	Bodyfiller	 Bodyfiller
	Dry wall lining boards	 Dry wall lining boards
	Lacquers	Lacquer
	Mineral materials	 Solid surface material
	Plaster	 Plaster
	Primer filler	• Primer filler
	Wood	 Hard wood
	Wood	 Soft wood
	Wood	 Resinous wood
Furniture Production:	Coatings	Lacquer
	Plastics	 Solid surface material
Automotive:	Bodyfiller	Bodyfiller
	Composites	 Glass-fibre reinforced plastic (GRP)
	Gelcoats	 Gelcoat polyester
	Lacquers	• Lacquer
	Lacquers	Old lacquer
	Paints	Colour
	Plastics	 Plastics
	Plastics	 Acrylic glass
	Primer filler	• Primer filler
	Primers	 Primer coat
	Primers	 Epoxy primer coat
	Primers	Cathodic dip primer coat
Aerospace:		Colour
		• Primer filler
		Old lacquer
	Acrylic glass (Plexiglass)	Acrylic glass
	Bodyfiller	Bodyfiller
	Composites	 Glass-fibre reinforced plastic (GRP)
	Gelcoats	 Gelcoat polyester
	Lacquers	Lacquer
	Plastics	Plastics
	Primers	• Primer coat
	Primers	• Epoxy primer coat
	Primers	Cathodic dip primer coat

Conversion forms	Upper conversion	Lower conversion
	Rolls	- Jumbolino - Paper rolls - siafast rolls - siasoft rolls
	Strips	- siafast strips - siasoft strips



Conversion forms	Upper conversion	Lower conversion
	Delta and polygons	- Delta and polygons
	Discs	 Daisy discs siafast discs siasoft discs Self-adhesive discs Various discs
	Belts	 Hand sanding belts and sleeves (width: 30–390 mm/length: up to 950 mm) Narrow, edge and long belts (width: 25–399 mm/length: up to 10,700 mm) Tongued sanding belts (width: 6–30 mm/length: up to 950 mm)

Application	Superordinate group	Subgroup
Ð	Portable machine sanding	random orbital sander
	Portable machine sanding	Orbital sanders
B	Portable machine sanding	Delta sander
	Manual sanding	Manual sanding
	Manual sanding	Hand sanding with sanding block
	Stationary machine sanding	Rolls
Cut:	Dry application	

Details		
No suitability for:	- glass sanding - Wet sanding - Stone grinding	
Sanding recommendation:		
Safety recommendation:	n: Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertis > Safety	
	 Pay attention to the abrasives safety data sheet (available from sia Abrasives) Follow the general FEPA safety recommendations Use eye and face protection 	
	- Use an effective dust extraction unit or wear a fine dust mask	



Communication			
Claim:	For a perfect finish at full speed		
Сору:	The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.		
Image material:	Product Top View (PTV)	Front side: Rear side:	ID ID
	Application image	Building Interior: Furniture Production: Automotive: Aerospace:	ID 342 ID 341 ID 8855 ID 9271
	Product show:		
	Macro shot:		
	Packaging image:		
	Product group image:		ID 1656

Main applicationSecondary application