Technical data sheet 4570 siabite X



Status:	Ok
Approval:	03.06.2021

Classification	Public series
Product type:	Coated abrasives
Main industries:	General Fabrication
Further industries:	Containers Machinery, equipment Casting and Forging Shipbuilding

Product profile		
Grit type:	Ceramic aluminium oxide	
Grit range (total):	36; 60-80; 120	
Backing:	Fibre	
Coating:	Electrostatic	
Bonding:	Resin over resin	
Special coating:	Cooling additive	
Equipment:		

Properties		Technology
Removal rate:	10 - very high	- X-Technology
Lifetime:	10 - very long	
Finishing:	9 - very good	
Flexibility:	1 - very rigid	
Contact pressure:	9 - high	

Advantages		
General Fabrication:	Cool cutUniform cutting performanceLong lifetimeFine surface finish	

Applications	
General Fabrication:	Weld removalRemoval of scale and mill scaleBlending flawsRemoving discolouration

Material			
General Fabrication:	Non-ferrous metals	Aluminium	
	Stainless steel	 High-alloy steels 	
	Steel	 Unalloyed / low-alloy steel 	

Technical data sheet 4570 siabite X



Conversion forms	Upper conversion	Lower conversion	
	Discs	- Fibre discs	

Application	Superordinate group	Subgroup
Ø.	Portable machine sanding	Angle grinder
Cut:	Dry application	

Details	
No suitability for:	- Wet sanding - Stone grinding
Sanding recommendation:	- For aggressive grinding, select a hard sanding pad
Safety recommendation:	Observe the current valid safety recommendations at: www.sia-abrasives.com > Expertise > Safety
	 Pay attention to the abrasives safety data sheet (available from sia Abrasives) Follow the general EN safety recommendations Follow the general FEPA safety recommendations Use eye and face protection

Communication				
Claim:	The fibre disc for the coolest grinding with new and unique X-Technology			
Сору:	Thanks to innovative X-Technology, the 4570 siabite fibre disc brings you considerably cooler grinding with a long service life and a consistent cutting performance on stainless steel and mild steel. With new and unique X-Technology, an active cooling aid is applied directly to the top level, which enhances cooling and minimises discolouration.			
Image material:	Product Top View (PTV)	Front side: Rear side:	ID ID	
	Application image	General Fabrication:	ID 9012	
	Product show:			
	Macro shot:			
	Packaging image:	<u> </u>		
	Product group image:		ID 8994	

Main applicationSecondary application