

# Technical data sheet

7940 siaair



Status:	Ok
Approval:	23.08.2023

<b>Classification</b>	
Public series	
Product type:	Coated abrasives
Main industries:	Automotive Aerospace Building Interior
Further industries:	Trucks Rail Marine Bus Wind Power Kitchens Sports Equipment

<b>Product profile</b>	
Grit type:	Aluminium oxide
Grit range (total):	240; 360; 500-1000; 1500-2000; 3000-4000
Backing:	Knitted fabric with foam backing
Coating:	Special process
Bonding:	Resin over resin
Special coating:	
Equipment:	




<b>Properties</b>		<b>Technology</b>
Removal rate:	8 - high	- siafast
Lifetime:	8 - long	
Finishing:	8 - good	
Flexibility:	10 - highly flexible	
Contact pressure:		



<b>Advantages</b>	
Building Interior:	<ul style="list-style-type: none"><li>- Waterproof and washable</li><li>- Very long lifetime</li><li>- Low scratch depth</li><li>- Low clogging</li><li>- Can be used many times</li><li>- Absorbs water</li><li>- Permeable to air and water</li><li>- Pressure-equalising foam gives perfect surface finish</li></ul>

<b>Advantages</b>	
Automotive:	<ul style="list-style-type: none"> <li>- High stock removal rates and excellent finish</li> <li>- Low clogging thanks to damp sanding</li> <li>- Highly adaptable to contours, curves and profiles</li> <li>- Pressure-equalising foam gives perfect surface finish</li> <li>- Waterproof and washable</li> <li>- Resistant to silicon remover</li> </ul>
Aerospace:	<ul style="list-style-type: none"> <li>- High stock removal rates and excellent finish</li> <li>- Low clogging thanks to damp sanding</li> <li>- Very long lifetime</li> <li>- Highly adaptable to contours, curves and profiles</li> <li>- Pressure-equalising foam gives perfect surface finish</li> <li>- Waterproof and washable</li> <li>- Resistant to silicon remover</li> </ul>

<b>Applications</b>	
Building Interior:	
Automotive:	<ul style="list-style-type: none"> <li>- Matt finishing of conventional old and new varnishes as well as composite materials</li> <li>- Fine sanding of primer filler in hard-to-reach areas</li> <li>- Preparation for polishing on high-gloss surfaces</li> </ul>
Aerospace:	<ul style="list-style-type: none"> <li>- Matt finishing of scratch-resistant coating systems as well as composite materials</li> <li>- Fine sanding of primer filler in hard-to-reach areas</li> <li>- Preparation for polishing on high-gloss surfaces</li> <li>- Producing a matt finish for blending</li> </ul>

<b>Material</b>															
Building Interior:	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;">Lacquers</td> <td style="width: 50%; border: none;"><input type="radio"/> Composite</td> </tr> <tr> <td style="border: none;">Mineral materials</td> <td style="border: none;"><input checked="" type="radio"/> Lacquer</td> </tr> <tr> <td style="border: none;">Paints</td> <td style="border: none;"><input checked="" type="radio"/> Solid surface material</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;"><input checked="" type="radio"/> Colour</td> </tr> </table>	Lacquers	<input type="radio"/> Composite	Mineral materials	<input checked="" type="radio"/> Lacquer	Paints	<input checked="" type="radio"/> Solid surface material		<input checked="" type="radio"/> Colour						
Lacquers	<input type="radio"/> Composite														
Mineral materials	<input checked="" type="radio"/> Lacquer														
Paints	<input checked="" type="radio"/> Solid surface material														
	<input checked="" type="radio"/> Colour														
Automotive:	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;">Composites</td> <td style="width: 50%; border: none;"><input type="radio"/> Composite</td> </tr> <tr> <td style="border: none;">Gelcoats</td> <td style="border: none;"><input checked="" type="radio"/> Gelcoat polyester</td> </tr> <tr> <td style="border: none;">Lacquers</td> <td style="border: none;"><input checked="" type="radio"/> Lacquer</td> </tr> <tr> <td style="border: none;">Lacquers</td> <td style="border: none;"><input checked="" type="radio"/> Old lacquer</td> </tr> <tr> <td style="border: none;">Paints</td> <td style="border: none;"><input checked="" type="radio"/> Colour</td> </tr> <tr> <td style="border: none;">Plastics</td> <td style="border: none;"><input checked="" type="radio"/> Plastics</td> </tr> <tr> <td style="border: none;">Plastics</td> <td style="border: none;"><input checked="" type="radio"/> Acrylic glass</td> </tr> </table>	Composites	<input type="radio"/> Composite	Gelcoats	<input checked="" type="radio"/> Gelcoat polyester	Lacquers	<input checked="" type="radio"/> Lacquer	Lacquers	<input checked="" type="radio"/> Old lacquer	Paints	<input checked="" type="radio"/> Colour	Plastics	<input checked="" type="radio"/> Plastics	Plastics	<input checked="" type="radio"/> Acrylic glass
Composites	<input type="radio"/> Composite														
Gelcoats	<input checked="" type="radio"/> Gelcoat polyester														
Lacquers	<input checked="" type="radio"/> Lacquer														
Lacquers	<input checked="" type="radio"/> Old lacquer														
Paints	<input checked="" type="radio"/> Colour														
Plastics	<input checked="" type="radio"/> Plastics														
Plastics	<input checked="" type="radio"/> Acrylic glass														
Aerospace:	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;"></td> <td style="width: 50%; border: none;">Colour</td> </tr> <tr> <td style="border: none;"></td> <td style="border: none;">Old paint</td> </tr> <tr> <td style="border: none;">Acrylic glass (Plexiglass)</td> <td style="border: none;">Acrylic glass</td> </tr> <tr> <td style="border: none;">Composites</td> <td style="border: none;">Composite</td> </tr> <tr> <td style="border: none;">Gelcoats</td> <td style="border: none;">Gelcoat polyester</td> </tr> <tr> <td style="border: none;">Lacquers</td> <td style="border: none;">Lacquer</td> </tr> </table>		Colour		Old paint	Acrylic glass (Plexiglass)	Acrylic glass	Composites	Composite	Gelcoats	Gelcoat polyester	Lacquers	Lacquer		
	Colour														
	Old paint														
Acrylic glass (Plexiglass)	Acrylic glass														
Composites	Composite														
Gelcoats	Gelcoat polyester														
Lacquers	Lacquer														

<b>Conversion forms</b>	Upper conversion	Lower conversion
	Rolls	- Jumbolino
	Strips	- siafast strips
	Discs	- siafast discs

<b>Application</b>	Superordinate group	Subgroup
	Portable machine sanding	random orbital sander
	Manual sanding	Manual sanding
Cut:	Wet sanding	

<b>Details</b>	
No suitability for:	<ul style="list-style-type: none"> <li>- glass sanding</li> <li>- Ceramic lacquers</li> <li>- Stone grinding</li> </ul>
Sanding recommendation:	- Best results are obtained by damp grinding
Safety recommendation:	<p>Observe the current valid safety recommendations at: <a href="http://www.sia-abrasives.com">www.sia-abrasives.com</a> &gt; Expertise &gt; Safety</p> <ul style="list-style-type: none"> <li>- Pay attention to the abrasives safety data sheet (available from sia Abrasives)</li> <li>- Follow the general FEPA safety recommendations</li> <li>- Use eye and face protection</li> <li>- Use an effective dust extraction unit or wear a fine dust mask</li> </ul>

<b>Communication</b>			
Claim:	A perfect finish for varnishes and mineral materials		
Copy:	Whether it's scuffing, fine sanding or preparation for polishing – the improved technology of 7940 siaair is the key to a perfect finish in damp sanding applications.		
Image material:	Product Top View (PTV)	Front side: ID	Rear side: ID
	Application image	Building Interior:	ID 8357
		Automotive:	ID 147
		Aerospace:	ID 9271
	Product show:		
	Macro shot:		ID 5109
Packaging image:			
Product group image:			ID 1693

- Main application
- Secondary application