



2918 siapan

The segmented belt for the solid wood material industry



The segmented belt for the solid wood material industry

The 2918 siapan, which has been specially designed for the solid wood material industry, offers top results as a segmented

- Dust-free process: Antistatic construction minimises dust build-up on belt, workpiece and machinery
- High transverse belt stability
- High removal rate when working on softwood and hardwood with coarser grits
- Can be repeatedly clamped and unclamped on the machine
- Waterproof and washable
- Can be used as wide belt and segmented belt
- Perfect surfaces thanks to TopTec
- For continuous, very heavy-duty use, washable
- ▶ High tearing resistance

Product profile

Grit type: Semi-friable aluminium oxide

Grit range: 36-40; 60-120 Backing: Z-wt cloth, polyester

P036 - P060 Coating: Electrostatic open

P080 - P120 Closed

Bonding: Resin over resin Equipment: TopTec

Use







Fine sanding

Intermediate sanding

Applications

Calibrating

- Keying of plywood, wood core plywood and solid wood panels
- Calibrating solid wood
- Calibrating solid wood
- Calibrating, coarse and intermediate sanding
- Coarse sanding in plywood manufacturing
- Coarse sanding of laminated solid wood panels
- Fine sanding of laminated solid wood panels

Materials

Hard wood; Soft wood; Resinous wood; Wooden base; Wooden base

Technology

TopTec

