



1950 siaspeed

For a perfect finish at full speed

1950 siaspeed

Building Interior



For a perfect finish at full speed

The versatile all-round product 1950 siaspeed is specially designed for high stock removal rates, perfect surface quality and long life in applications such as the surface treatment of body filler, primer filler, lacquers and paints.

- A versatile all-round product
- High performance for stock removal
- Longest lifetime
- Minimal clogging thanks to open coating in 220 600 grit range

Product profile

Grit type:	Mixed grit with ceramic content	40 - 80
	Semi-friable aluminium oxide / blue-fired	P100 - P400
	White aluminium oxide	P500 - P1500
Grit range:	40; 60-1500	
Backing:	Paper (FSC-certified)	40 – P600
-	Film	P800 - P1500
Coating:	Electrostatic	40 - P180
•	Electrostatic open	P220 - P600
	Special process	P800 - P1500
Bonding:	Resin over resin	
Special coating:	Stearate	from 80

Use



Applications

- Keying or sanding surfaces
- Sanding off old paint and varnish
- Keying smoothed surfaces
- Fine sanding of surfaces
- Flatting uneven areas

Materials

Lacquer; Hard wood; Soft wood; Solid surface material; Primer filler; Bodyfiller; Resinous wood; Plaster; Dry wall lining boards; Plastics

Technology

Open coating; Plain; S Performance; siafast; siasoft

